

GSID200A120S3B1

IGBT Module




Features:

- Low Saturation Voltage: $V_{CE(sat)} = 1.80V @ I_C = 200A, T_C = 25^\circ C$
- Low Switching Loss
- 100% RBSOA Tested ($2 \times I_C$)
- Low Stray Inductance
- Lead Free, Compliant with RoHS Requirement



Applications:

- Welding Machine/ Cutting Machine
- Induction Heating
- Ultrasonic Device
- UPS



Maximum Rated Values of IGBT ($T_C = 25^\circ C$ unless otherwise specified)

V_{CES}	Collector-Emitter Blocking Voltage		1200	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_C	Continuous Collector Current	$T_C = 80^\circ C$	200	A
		$T_C = 25^\circ C$	400	A
I_{CM}	Repetitive Peak Collector Current	$T_J = 175^\circ C$	400	A
P_D	Maximum Power Dissipation per IGBT	$T_C = 25^\circ C$ $T_{Jmax} = 175^\circ C$	1595	W

Electrical Characteristics of IGBT ($T_C=25^\circ\text{C}$ unless otherwise specified)

Static characteristics

Symbol	Description	Conditions	Min	Typ	Max	Unit	
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C = 10\text{mA}$, $V_{CE} = V_{GE}$	3.0	4.0	6.0	V	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = 200\text{A}$, $V_{GE} = 15\text{V}$	$T_J = 25^\circ\text{C}$		1.80	2.00	V
			$T_J = 125^\circ\text{C}$		1.90		V
			$T_J = 150^\circ\text{C}$		2.00		V
I_{CES}	Collector-Emitter Leakage Current	$V_{GE} = 0\text{V}$, $V_{CE} = V_{CES}$, $T_J = 2^\circ\text{C}$			1	mA	
I_{GES}	Gate-Emitter Leakage Current	$V_{GE} = \pm 20\text{V}$, $V_{CE} = 0\text{V}$, $T_J = 25^\circ\text{C}$			200	nA	
C_{ies}	Input Capacitance	$V_{CE} = 25\text{V}$, $V_{GE} = 0\text{V}$, $f = 1\text{MHz}$		20.0		nF	
C_{oes}	Output Capacitance			1.08		nF	

Switching Characteristics

$t_{d(on)}$	Turn-on Delay Time	$V_{CC} = 600\text{V}$, $I_C = 200\text{A}$, $R_G = 15\ \Omega$, $V_{GE} = \pm 15\text{V}$, Inductive Load	$T_J = 25^\circ\text{C}$		1100		ns
			$T_J = 125^\circ\text{C}$		1080		
			$T_J = 150^\circ\text{C}$		1095		
t_r	Rise Time		$T_J = 25^\circ\text{C}$		200		ns
			$T_J = 125^\circ\text{C}$		205		
			$T_J = 150^\circ\text{C}$		219		
$t_{d(off)}$	Turn-off Delay Time		$T_J = 25^\circ\text{C}$		900		ns
			$T_J = 125^\circ\text{C}$		950		
			$T_J = 150^\circ\text{C}$		963		
t_f	Fall Time		$T_J = 25^\circ\text{C}$		110		ns
			$T_J = 125^\circ\text{C}$		140		
			$T_J = 150^\circ\text{C}$		150		
E_{on}	Turn-on Switching Loss	$T_J = 25^\circ\text{C}$		19.00		mJ	
		$T_J = 125^\circ\text{C}$		22.90			
		$T_J = 150^\circ\text{C}$		24.11			

E _{off}	Turn-off Switching Loss	V _{CC} = 600V, I _C = 200A, R _G = 15 Ω, V _{GE} = ±15V, Inductive Load	T _J = 25°C		15.20		mJ
			T _J = 125°C		19.60		
			T _J = 150°C		20.43		
Q _g	Total Gate Charge		T _J = 25°C		2100		nC
			T _J = 125°C		2130		
			T _J = 150°C		2145		
R _{gint}	Internal Gate Resistance		T _J = 25°C	1.9	2.5	3.1	Ω
RBSOA	Reverse Bias Safe Operation Area	I _C =400A, V _{CC} =1050V, V _p =1200V, R _g = 15Ω, V _{GE} =+15V to 0V, T _J =150°C	Trapezoid				
R _{θJC}	IGBT Thermal Resistance: Junction-To-Case				0.094		°C/W

Maximum Rated Values of Diode (T_C=25°C unless otherwise specified)

V _{RRM}	Repetitive Peak Reverse Voltage	1200	V
I _F	Diode Continuous Forward Current	200	A
I _{FM}	Diode Maximum Forward Current	400	A

Electrical Characteristics of Diode (T_C=25°C unless otherwise specified)

Symbol	Description	Conditions	Min	Typ	Max	Unit
V _{FM}	Forward Voltage	I _F = 200A , V _{GE} = 0V	T _J = 25°C		2.10	V
			T _J = 125°C		2.15	
			T _J = 150°C		2.10	
I _{rr}	Peak Reverse Recovery Current	I _F = 200A, di/dt = 960A/μs, V _{rr} = 600V, V _{GE} = -15V	T _J = 25°C		65	A
			T _J = 125°C		105	
			T _J = 150°C		118	
Q _{rr}	Reverse Recovery Charge		T _J = 25°C		9.65	μC
			T _J = 125°C		21.80	
			T _J = 150°C		23.10	

E _{rec}	Reverse Recovery Energy	I _F = 200A, di/dt = 960A/μs, V _{rr} = 600V, V _{GE} = -15V	T _J = 25°C	3.20	mJ
			T _J = 125°C	8.20	
			T _J = 150°C	8.74	
R _{θJC}	Diode Thermal Resistance: Junction-To-Case			0.165	°C/W

Module

Symbol	Description		Min	Typ	Max	Unit
V _{iso}	Isolation Voltage(All Terminals Shorted)	f = 50Hz, 1minute	2500			V
T _J	Maximum Junction Temperature				175	°C
T _{JOP}	Maximum Operating Junction Temperature Range		-40		+150	°C
T _{stg}	Storage Temperature		-40		+125	°C
R _{θCS}	Case-To-Sink (Conductive Grease Applied)			0.03		°C/W
T	Power Terminals Screw:M6		4.0		6.0	N·m
T	Mounting Screw:M6		4.0		6.0	N·m
G	Weight			230		g




Fig.1 Typical Saturation Voltage Characteristics




Fig.2 Typical Output Characteristics




Fig.3 Forward Characteristics of Diode




Fig.4 Reverse Bias Safe Operation Area (RBSOA)




Fig.5 Typical Switching Loss vs. Collector Current




Fig.6 Typical Switching Loss vs. Collector Current




Fig.7 Typical Switching Loss vs. Gate Resistance




Fig.8 Typical Switching Loss vs. Gate Resistance




Fig.9 Transient thermal impedance (IGBT)




Fig.10 Transient thermal impedance (Diode)




Fig.11 Typical Load Current vs. Frequency






Fig.12 Capacitance Characteristics

Internal Circuit



Package Outline (Unit: mm):



Revision History

Date	Revision	Notes
04/13/2015	1.0	Initial release
11/17/2015	2.0	Add Tj=150°C test data, etc.

Global Power Technologies Group

20692 Prism Place
 Lake Forest, CA 92630
 TEL (949) 207-7500
 FAX (949) 613-7600
 E-mail: info@gptechnology.com
 Web site: www.gptechnology.com



Notes

- **RoHS Compliance**
 The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented March, 2013. RoHS Declarations for this product can be obtained from the Product Documentation sections of www.gptechnology.com.
- **REACH Compliance**
 REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact our office at GPTG Headquarters in Lake Forest, California to insure you get the most up-to-date REACH SVHC Declaration.
 REACH banned substance information (REACH Article 67) is also available upon request.
- This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, or air traffic control.
- To obtain additional technical information or to place an order for this product, please contact us. The information in this datasheet is provided by Global Power Technologies Group. GPTG reserves the right to make changes, corrections, modifications, and improvements of datasheet without notice.